

Index

A

- abrupt responses 22, 29
- absorption of variability 79, 81, 83
- accuracy
 - auto tuner 1
 - measurement (*see measurement resolution*)
 - tuning 1
- action
 - control 2–6
 - direct 2–6
 - fail-open 2–6
 - gain 8, 17, 19, 25, 127–128, 134, 137
 - on-off 131, 133, 140
 - process 3–6
 - rate 8, 17, 42, 67, 126, 128, 134, 137
 - reset 8, 17, 19, 23, 25–26, 66–67, 115, 118–119, 123, 128
 - reverse 4–6
 - valve 2–6
- actuator 94, 99
- adaptive control 147, 185–192
- adaptive controller 185–186, 188, 190–191

- advanced control tuning 9, 19
 - algorithm
 - error-squared 67
 - PID 10, 62
 - update time 139, 143–144
 - aliasing signal 139
 - analog controllers 210
 - analog output 213
 - block 4
 - analog to digital converter (A/D) 29, 33
 - signal 91
 - analyzer
 - cycle time 29
 - auto mode 6
 - auto tuner
 - accuracy 1
 - identification of dead band 115
 - integrator gain 53
 - pretest 117
 - relay method 115–116
 - automatic mode 2, 6
- ## B
- back-calculate
 - function blocks 4, 7
 - backlash 195
 - ball valve 94, 99

- batch control 147
 - tuning 9, 19
- bend 199, 203
- blending (*see pipeline and static mixer*) 150
- boilers 152
- boiling point 171
- bump 57, 66
- bumpless 7, 207, 212
- butterfly valve 15, 40, 94, 99

C

- calibration 92
- calibration span 14, 29, 42
- cas (cascade) mode 6
- cascade control 3, 9–10, 19
 - tuning 63, 125–129
- characteristic
 - valve 15, 25, 35, 41, 99–100, 126
- characterization
 - signal 99–100, 125
- chatter 29, 32
- closed loop 6–7, 62–63, 229
 - method tuning 66
- coating of sensor 91–92, 118
- coil inlet temperature 159
- coils 158
- column control
 - tuning 17, 22, 24–25, 28, 40, 123
 - valve 98
- compression 139, 143–144

- compressor control
 - tuning 41
 - valve 97–98
- compressor surge control 162
- compressors 162
- concentration control tuning 31, 33, 118, 126
- control
 - bump 57, 66
 - cascade 3, 6, 9–10, 19, 22
 - disturbance (*see also upset*) 34, 118, 123, 126
 - error 8, 31
 - feedback 2, 37, 118
 - feedforward 68, 122–125, 127
 - interaction 22–23, 67–68, 126, 129, 131–132
 - material balance 24
 - offset 15, 26, 127, 141
 - oscillations 19, 25–29, 38, 63, 99, 115, 118
 - overshoot 17, 26, 28, 134
 - performance 31, 37, 122, 126, 216
 - residence time 39, 41
 - resonance (loops) 131, 133
 - set point 8, 17, 19–21, 27
 - split-ranged 17
 - stability 25–26
 - upset (*see also disturbance*) 34, 67, 123, 126–127, 131, 133, 137, 139

- variability 1–2, 22, 31, 139
 - control action 2–6, 209
 - controlled variable 14, 42, 120
 - controller output 209
 - function blocks 4, 15
 - PID 15, 66
 - conveyor control tuning 22, 28
 - crystallizer control tuning 17, 24–25
 - crystallizers 164
 - current-to-pneumatic transducer (I/P) 4
 - cycle time analyzer 29
- D**
- dead band 215
 - valve 2, 22–23, 33, 37, 62–63, 66, 94, 100
 - dead time 194
 - of valve 62, 99–100
 - dead time dominant 241
 - response 19, 22, 39–40, 67, 133, 140
 - dead time or time delay
 - response 33–38, 118–120, 122, 125, 128
 - dead time to time constant ratio 19, 39
 - dead-time compensator tuning 118–122, 140
 - delay 193, 195
 - from transportation 37, 118–119
 - derivative action (*see rate*)
 - derivative mode 8
 - desuperheater control tuning 22, 41–42
 - different objectives 245, 247
 - difficult situations 76, 245, 247
 - digital positioner 94, 100
 - direct action 2–6
 - direct digital control (DDC) 8
 - distillation (*see column control*)
 - distillation columns 166
 - disturbance control (*see also upset*) 34, 118, 123, 126
 - drift sensor 91–92
 - dryers 169
 - dynamic classes
 - valve 97
- E**
- equations 228
 - error control 8, 31
 - error-squared algorithm 67
 - evaporator control tuning 17, 24, 127
 - evaporators 171
 - extruders 172
- F**
- faceplate
 - PID 17
 - fail open 209

- valve 4, 6
- falter or hesitate response 19, 133
- feedback control 2, 37, 118
- feedforward control 68, 122–125, 127
- feedwater flow controller 155
- fermentors 175
- fieldbus function blocks 4, 10
- fieldbus mode 6, 8
- filter 9, 15, 22, 31, 66, 123, 126, 128
- first order plus dead time 228
- flow (feed) ratio 40
- flow control tuning 22, 67, 115, 119, 126
- fluctuations or waves
 - pressure 131, 133
- function blocks
 - back-calculate 4, 7
 - controller output 15
 - fieldbus 4, 10
 - PID 4

G

- gain action 8, 17, 19, 25, 127–128, 134, 137
- gain tuning 8, 22–28, 39, 62–63, 66–67, 137, 141–142
- general-purpose method
 - tuning 62–63

H

- Harriott, Peter 232
- HART 212

- heat exchanger control
 - tuning 22, 40, 42
- heat exchangers 176
- heat transfer 160
- historian
 - compression 139
 - update time 139

I

- identification of dead band 115
- inc-close 209
- inc-open 209
- increase-to-close valve 4–6
- initialization manual (IMan)
 - mode 7
- integral action (*see reset*)
- integral mode 8
- integrated error 238
- integrating process 76, 193, 200
- integrating process gain 48–51, 59, 78–79, 84, 199, 201, 206, 239, 242
- integrating response 62, 141
- integrator gain
 - for auto tuner 53
- integrator response 53–54
- interaction 126, 129
 - control 22–23, 67–68, 131–132
- inverse response 29, 67–68, 120, 123, 125

- J**
jackets 158
- L**
lag (*see time constant*) 193, 203, 211
thermowell 33
- Lambda**
arrest time 79, 89, 247
closed loop time constant 73, 89, 130, 181
integrating process 58–59, 76–81, 83–84, 88–89, 168, 179, 193, 199, 201, 205–206, 222, 239–240, 247
self-regulating process 42, 69–71, 74, 76, 81, 88, 127, 129, 140–141, 150–151, 159, 162–165, 167, 170, 172, 174, 177, 180–182, 184, 193, 198–199, 204, 220, 222, 239, 241, 243
- Lambda as a multiple of dead time** 155
- Lambda for different objectives and difficult situations** 75, 245–247
- Lambda self-regulating process method** 39, 42, 127, 129
- lead time** 211
- level control** 23–24, 66, 68, 81, 83, 98, 115, 140, 142, 152–156, 166–169
- level control valve** 92, 98, 100
- level switches** 131, 137, 140
- limits**
output 66, 128–129
set point range 128–129
set point rate limits 23
set point rate of change 9
set point velocity 67
- load disturbance rejection** 227
- load disturbances** 230
- local mode** 6
- local override mode** 7
- loop**
closed 6–7, 62–63
master (*also known as primary*) 8
open 7, 62
primary (*also known as master*) 8
secondary (*also known as slave*) 8, 63, 125–129
slave (*also known as secondary*) 8, 63, 125–129
troubleshooting 131–216
- loop performance** 195
estimating 193

M

maintenance
 of valve 92, 100–101
manipulated variable 3, 10,
 14, 25, 32, 35, 40
manual (Man) mode 7
master loop (*also known as
 primary*) 8, 125–129
master temperature
 controller 165
material balance control 24
maximum disturbance
 rejection 231
measurement gain 197
measurement resolution 31,
 143–144
methods
 tuning 1, 19
minimum integrated error
 230
mode
 auto 6
 automatic 2, 6
 cascade (Cas) 6
 derivative 8
 direct digital control
 (DDC) 8
 fieldbus 6, 8
 initialization manual
 (IMan) 7
 integral 8
 local (*see auto*) 6
 local override (LO) 7
 manual (Man) 7

operational 6
output tracking 7
proportional 8–15
remote (*see cascade*) 7
remote cascade (RCas) 7
remote output (ROut) 8
remote set point (RSP) 7
supervisory 7
model predictive control (*see
 constrained multivariable
 predictive control*) (MPC)
 157, 215

N

near integrating 204, 239
neutralizers 178
noise 194
noise signal 22, 29, 34, 53, 66,
 91, 99
nonlinearity response 1, 41,
 62, 125–126

O

observed response 194
offset control 15, 26, 127, 141
on-off action 131, 133, 140
open loop 7, 62, 229
 gain 35–50, 197–199
 gain response 38–53
 response 194
 test 197
 time constant 196, 232
operational mode 6
optimum integral time 241

- oscillations 19, 25–26, 28, 38, 63, 99, 115, 118
 - control and response 19
- output limits 66, 128–129
- output tracking 7
- overshoot control 17, 26, 28, 134
- oxygen controller 156
- oxygen sensor 157
- P**
- patterns of response 123
- peak error 229, 231, 238
- performance
 - control and tuning 31, 37, 122, 126, 216
- pH control
 - tuning 29, 33, 35, 40
 - valve 98, 118
- pH measurement 178
- PID**
 - algorithm 10, 62, 197
 - checklist 207
 - controller output 15, 66
 - controllers 210, 227
 - faceplate 17
 - function blocks 4
 - scan time 32–33, 60–61, 91, 115, 126, 128, 139, 143
 - structure mode 210
- pipeline control tuning 22, 28, 31, 42, 119
- positioner
 - digital 94, 100
 - pneumatic 94, 99
 - smart (*see digital positioner*)
 - valve 4, 92–100
- power spectrum signal 137–138
- pressure
 - fluctuations or waves 131, 133
- pressure control
 - tuning 19, 28, 39, 41, 63, 66, 115, 126, 133
 - valve 97, 100
- pressure waves 131, 133
- pretest
 - auto tuner 117
- primary controller output 211
- primary loop (*also known as master loop*) 8, 125–129, 213
- process
 - action 3–6
 - dynamics 186
 - gain 197
 - integrating 76, 193, 200, 242
 - response 193
 - runaway 193, 202–203
 - self-regulating 193, 241
 - variable 2–3, 8, 10, 17, 22, 31, 35, 40, 66, 118, 120
- proportional action (*see gain*)

proportional band tuning 23
proportional mode 8–15
pseudo integrating 204, 239
pulp and paper control
tuning 23
pump control tuning 41

Q

quarter-amplitude response
24–25

R

ramp rate 53–54, 141, 143
rate
tuning 8, 29–31, 62
rate action 8, 17, 31, 42, 67,
126, 128, 134, 137
rate time to dead time ratio
67
ratio
dead time to time
constant 19, 39, 140
flow (feed) 40
rate time to dead time 67
reset time to oscillation
period 28, 63, 67
signal-to-noise 91
reactor control tuning 17, 19,
24–25, 66, 127, 141
reactors 179
relay method
auto tuner 115–116
remote cascade 181
mode 7
remote mode (*see cascade*) 7

remote output (ROut) 193
mode 8
remote set point (RSP) 7
reset action 8, 17, 19, 23, 25–
26, 66–67, 115, 118–119,
123, 128
reset time to oscillation
period ratio 28, 63, 67
reset tuning 17, 25–39, 62
residence time control 39, 41
resistance temperature
detectors 91
resolution
limits 196
measurement 31, 143–
144
valve 31–32, 92, 99
response
abrupt 22, 29
analyzers 29
chatter 32
dead time or time delay
118–120, 122, 125, 128
dead-time dominant 19,
21–22, 39–40, 67, 133,
140
falter or hesitate 19, 133
integrating 62, 141
integrator 53–54
inverse 29, 67–68, 120,
123, 125
nonlinearity 1, 41, 62,
125–126
oscillations 99

- patterns 123
- quarter-amplitude 24–25
- runaway 62, 66, 141
- self-regulating 53
- sensor 91
- set point 63, 66–67
- smooth 22–23, 39, 118, 127
- staircase 29, 134
- steady state gain 120
- time constant 9, 19, 23, 31, 41, 53, 119–120, 125, 128
- time to steady state 94–97
- trajectory 17, 32
- reversal
 - of valve signal 4–6
- rotary valve 94, 99–100
- ROut 8, 12, 67, 163, 213
- runaway process 193, 202–203
- runaway response 62, 66, 141
- S**
- scan time 32–33, 60–61
 - PID 91, 115, 126, 128, 139, 143
- secondary (*also known as slave*) 8, 63, 125–129
- self-regulating process 43–44, 61, 69, 193, 198, 241
- self-regulating response 53
- sensitivity 194
- sensitivity of valve (*see valve resolution*)
- sensitivity to measurement (*see measurement resolution*)
- sensor
 - coating 91–92, 118
 - drift 91–92
 - response 91
- sequence control tuning 22
- series form 210
- set point 212
 - control 8, 17, 19–21, 27
 - range limits 128–129
 - rate limits (rate of change limits) (velocity limits) 9, 23, 67, 214
 - rate of change (*see rate limits*)
 - response 63, 66–67
 - velocity limits (*see rate limits*)
- settings for tuning 57, 60, 67
- shaft of valve 94, 96, 99–100
- sheet and web control tuning 22–23, 28, 182–184
- Shinskey, Greg 236
- shortcut tuning 115
- signal
 - aliasing 139
 - analog to digital converter (A/D) 29, 33, 91
 - characterization 99–100, 125

- current-to-pneumatic transducer (I/P) 4
 - filter 9, 15, 22, 31, 66, 123, 126, 128
 - filter time 213
 - noise 22, 29, 34, 53, 66, 91, 99
 - power spectrum 137–138
 - reversal 4–6
 - signal-to-noise ratio 91
 - size
 - step 57, 94, 97, 132, 143–144
 - slave loop (*also known as secondary*) 8, 63, 98, 125–129
 - sliding stem (globe) valve 100
 - smart positioner (*see digital positioner*)
 - smart transmitter 91–92
 - smooth response 22–23, 39, 118, 127
 - span
 - calibration 14, 29, 42
 - time 97
 - specification
 - valve 97
 - spinning (fibers) control
 - tuning 22
 - split range valve 98
 - split-ranged control 17
 - stability 25–26
 - staircase response 29, 134
 - standard form 87, 210
 - startup control tuning 19
 - static mixer control tuning
 - 22, 41–42
 - steady state gains (*see open loop gain*)
 - steam traps 131, 133
 - step change 193–194, 196
 - step size 57, 94, 97, 132, 143–144
 - stick-slip valve 35, 92, 134, 139
 - stiction 196
 - stroking time (*see valve response time*)
 - supervisory control tuning 7
 - supervisory mode 7
 - surge control 163–164
- T**
- temperature control
 - tuning 17, 26, 29, 32–33, 39, 63, 67
 - valve 98, 100
 - temperature detectors 91
 - temperature loop controls 159
 - thermowell lag 33
 - time constant 195, 197
 - response 9, 19, 23, 31, 34–42, 53, 119–120, 125, 128
 - time constant to dead time 232
 - time delay (*see dead time*)

- trajectory of response 17, 32
- transmitter
 - smart 91–92
- transportation delay 37, 118–119
- trend recording
 - compression 137, 144
 - update time 137, 144
- troubleshooting loop 131–216
- tuning
 - accuracy 1
 - advanced control 9, 19
 - batch control 9, 19
 - boilers 152–157
 - cascade control 63, 125–129
 - closed loop method 66
 - coils and jackets 158–160
 - column control 17, 22, 24–25, 28, 40, 123, 166–168
 - compressor control 41, 162–163
 - concentration control 31, 33, 118, 126
 - conveyor control 22, 28
 - crystallizer control 17, 24–25, 164, 166
 - dead-time compensator 118–122, 140
 - desuperheater 41
 - desuperheater control 22, 42
 - dryers 169–170
 - evaporator control 17, 24, 127, 171
 - extruders 172–174
 - fermentors 175–176
 - flow control 22, 67, 115, 119, 126
 - gain 39, 62–63, 66–67, 137, 141–142
 - general-purpose method 62–63
 - heat exchanger control 22, 40, 42, 176–177, 179
 - integrating process 242–243
 - level 22–24, 28, 33, 66, 68
 - pH control 29, 33, 35, 40, 178
 - pipeline control 22, 28, 31, 42, 119
 - pressure control 19, 28, 39, 41, 63, 66, 115, 126, 133
 - proportional band 23
 - pulp and paper control 23
 - pump control 41
 - rate 8, 62
 - reactor control 17, 19, 24–25, 66, 127, 141, 179–180, 182
 - remote cascade 181–182
 - reset 17, 25–39, 62
 - runaway process 243

- sequence control 22
- settings 57, 60, 67
- sheet (web) control 22–23, 28, 182–184
- shortcut 115
- slave loop 8, 63, 98, 125–129
- spinning (fibers) control 22
- startup control 19
- static mixer control 22, 41–42
- supervisory control 7
- temperature control 17, 26, 29, 32–33, 39, 63, 67
- web control 22, 28
- window of allowable controller gains 62
- window of allowable gains 25
- Ziegler-Nichols 24, 63
- tuning methods 1, 19, 62
- tuning settings 193

U

- unidirectional 148–149
- update time of algorithm 139, 143–144
- upset control (*see also disturbance*) 67, 123, 126–127, 131, 133, 137, 139

V

- valve
 - action 209
 - actuator 94, 99
 - ball 94, 99
 - butterfly 15, 40, 94, 99
 - characteristic 15, 25, 35, 41, 99–100, 126
 - column control 98
 - compressor control 97–98
 - dead band 2, 22–23, 33, 37, 62, 63, 66, 94, 100
 - dead time 62, 99–100
 - dynamic classes 97
 - fail-open 4, 6
 - level control 92, 98, 100
 - maintenance 92, 100–101
 - pH control 98, 118
 - positioner 4, 92–100
 - pressure control 97, 100
 - resolution 31–32, 92, 99
 - response time 94–97
 - rotary 94, 99–100
 - shaft design 94, 96, 99–100
 - size 14
 - sliding stem (globe) 100
 - specification 97
 - split range 98
 - stick-slip 35, 92, 134, 139
 - temperature control 98, 100
- variability 1–2, 22, 31, 139

variable
 controlled 14, 42, 120
 manipulated 3, 10, 14, 25,
 32, 35, 40
 process 2–3, 8, 10, 17, 22,
 31, 35, 40, 66, 118, 120
variable speed drive (VSD) 3,
 40, 43–44, 46–47, 72, 82
velocity 158

W

waves
 pressure 131, 133
web and sheet control 22–23,
 28, 182–184
window of allowable
 controller gains 25, 62,
 83–85, 142–143, 243

Z

Ziegler-Nichols
 tuning 24, 63